

---

# **Adafruit AMG88xx Library Documentation**

***Release 1.0***

**Dean Miller**

**Aug 27, 2019**



---

## Contents

---

<b>1</b>	<b>Dependencies</b>	<b>3</b>
<b>2</b>	<b>Usage Example</b>	<b>5</b>
<b>3</b>	<b>Contributing</b>	<b>7</b>
<b>4</b>	<b>Building locally</b>	<b>9</b>
<b>5</b>	<b>Table of Contents</b>	<b>11</b>
5.1	Pixel test . . . . .	11
5.2	adafruit_amg88xx - AMG88xx GRID-Eye IR 8x8 IR sensor . . . . .	11
5.2.1	Implementation Notes . . . . .	12
<b>6</b>	<b>Indices and tables</b>	<b>13</b>
	<b>Python Module Index</b>	<b>15</b>
	<b>Index</b>	<b>17</b>



Adafruit CircuitPython module for the AMG88xx GRID-Eye IR 8x8 thermal camera.



# CHAPTER 1

---

## Dependencies

---

This driver depends on:

- [Adafruit CircuitPython](#)
- [Bus Device](#)
- [Register](#)

Please ensure all dependencies are available on the CircuitPython filesystem. This is easily achieved by downloading the [Adafruit library and driver bundle](#).





## CHAPTER 2

---

### Usage Example

---

Of course, you must import the library to use it:

```
import busio
import adafruit_amg88xx
```

The way to create an I2C object depends on the board you are using. For boards with labeled SCL and SDA pins, you can:

```
import board
```

You can also use pins defined by the onboard microcontroller through the `microcontroller.pin` module.

Now, to initialize the I2C bus:

```
i2c_bus = busio.I2C(board.SCL, board.SDA)
```

Once you have created the I2C interface object, you can use it to instantiate the AMG88xx object

```
amg = adafruit_amg88xx.AMG88XX(i2c_bus)
```

You can also optionally use the alternate i2c address (make sure to solder the jumper on the back of the board if you want to do this)

```
amg = adafruit_amg88xx.AMG88XX(i2c_bus, addr=0x68)
```

Pixels can be then be read by doing:

```
print(amg.pixels)
```



## CHAPTER 3

---

### Contributing

---

Contributions are welcome! Please read our [Code of Conduct](#) before contributing to help this project stay welcoming.



## CHAPTER 4

---

### Building locally

---

To build this library locally you'll need to install the `circuitpython-travis-build-tools` package.

Once installed, make sure you are in the virtual environment:

Then run the build:



### 5.1 Pixel test

Ensure your device works with this test:

Listing 1: examples/amg88xx\_simpletest.py

```
1 import time
2 import busio
3 import board
4 import adafruit_amg88xx
5
6 i2c = busio.I2C(board.SCL, board.SDA)
7 amg = adafruit_amg88xx.AMG88XX(i2c)
8
9 while True:
10     for row in amg.pixels:
11         # Pad to 1 decimal place
12         print(['{0:.1f}'.format(temp) for temp in row])
13         print("")
14     print("\n")
15     time.sleep(1)
```

### 5.2 adafruit\_amg88xx - AMG88xx GRID-Eye IR 8x8 IR sensor

This library supports the use of the AMG88xx in CircuitPython.

Author(s): Dean Miller, Scott Shawcroft for Adafruit Industries. Date: June 2017 Affiliation: Adafruit Industries

## 5.2.1 Implementation Notes

### Hardware:

**Software and Dependencies:** \* Adafruit CircuitPython: <https://github.com/adafruit/circuitpython/releases> \* Adafruit's Register library: [https://github.com/adafruit/Adafruit\\_CircuitPython\\_Register](https://github.com/adafruit/Adafruit_CircuitPython_Register) \* Adafruit's Bus Device library: [https://github.com/adafruit/Adafruit\\_CircuitPython\\_BusDevice](https://github.com/adafruit/Adafruit_CircuitPython_BusDevice)

### Notes:

**class** adafruit\_amg88xx.**AMG88XX** (*i2c, addr=105*)

Driver for the AMG88xx GRID-Eye IR 8x8 thermal camera.

**pixels**

Temperature of each pixel across the sensor in Celsius.

Temperatures are stored in a two dimensional list where the first index is the row and the second is the column. The first row is on the side closest to the writing on the sensor.

**temperature**

Temperature of the sensor in Celsius



## CHAPTER 6

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`



### a

adafruit\_amg88xx, [11](#)



## A

`adafruit_amg88xx` (*module*), [11](#)

`AMG88XX` (*class in adafruit\_amg88xx*), [12](#)

## P

`pixels` (*adafruit\_amg88xx.AMG88XX attribute*), [12](#)

## T

`temperature` (*adafruit\_amg88xx.AMG88XX attribute*), [12](#)