
Adafruit SimpleIO Library Documentation

Release 1.0

Scott Shawcroft

Apr 10, 2020

Contents

1	Dependencies	3
2	Installing from PyPI	5
3	Usage Example	7
4	Contributing	9
5	Documentation	11
6	Table of Contents	13
6.1	Simple tests	13
6.2	<code>simpleio</code> - Simple, beginner friendly IO.	15
7	Indices and tables	19
	Python Module Index	21
	Index	23

SimpleIO features a number of helpers to simplify hardware interactions. Many of the functions and classes are inspired by Arduino APIs to make it easier to move to CircuitPython from Arduino.

CHAPTER 1

Dependencies

This driver depends on:

- [Adafruit CircuitPython](#)

Please ensure all dependencies are available on the CircuitPython filesystem. This is easily achieved by downloading the [Adafruit library and driver bundle](#).

CHAPTER 2

Installing from PyPI

On supported GNU/Linux systems like the Raspberry Pi, you can install the driver locally [from PyPI](#). To install for current user:

```
pip3 install adafruit-circuitpython-simpleio
```

To install system-wide (this may be required in some cases):

```
sudo pip3 install adafruit-circuitpython-simpleio
```

To install in a virtual environment in your current project:

```
mkdir project-name && cd project-name
python3 -m venv .env
source .env/bin/activate
pip3 install adafruit-circuitpython-simpleio
```


CHAPTER 3

Usage Example

See the examples in the *Simple tests* folder for usage.

CHAPTER 4

Contributing

Contributions are welcome! Please read our [Code of Conduct](#) before contributing to help this project stay welcoming.

CHAPTER 5

Documentation

For information on building library documentation, please check out [this guide](#).

6.1 Simple tests

Ensure your device works with these simple tests.

Listing 1: examples/simpleio_tone_demo.py

```
1  """
2  'tone_demo.py'.
3
4  =====
5  a short piezo song using tone()
6  """
7  import time
8  import board
9  import simpleio
10
11
12  while True:
13      for f in (262, 294, 330, 349, 392, 440, 494, 523):
14          simpleio.tone(board.A0, f, 0.25)
15          time.sleep(1)
```

Listing 2: examples/simpleio_shift_in_out_demo.py

```
1  """
2  'shift_in_out_demo.py'.
3
4  =====
5  shifts data into and out of a data pin
6  """
7
8  import time
9  import board
```

(continues on next page)

(continued from previous page)

```

10 import digitalio
11 import simpleio
12
13 # set up clock, data, and latch pins
14 clk = digitalio.DigitalInOut(board.D12)
15 data = digitalio.DigitalInOut(board.D11)
16 latch = digitalio.DigitalInOut(board.D10)
17 clk.direction = digitalio.Direction.OUTPUT
18 latch.direction = digitalio.Direction.OUTPUT
19
20 while True:
21     data_to_send = 256
22     # shifting 256 bits out of data pin
23     latch.value = False
24     data.direction = digitalio.Direction.OUTPUT
25     print("shifting out...")
26     simpleio.shift_out(data, clk, data_to_send, msb_first=False)
27     latch.value = True
28     time.sleep(3)
29
30     # shifting 256 bits into the data pin
31     latch.value = False
32     data.direction = digitalio.Direction.INPUT
33     print("shifting in...")
34     simpleio.shift_in(data, clk)
35     time.sleep(3)

```

Listing 3: examples/simpleio_map_range_simpletest.py

```

1 """
2 'map_range_demo.py'.
3
4 =====
5 maps a number from one range to another
6 """
7 import time
8 import simpleio
9
10 while True:
11     sensor_value = 150
12
13     # Map the sensor's range from 0<=sensor_value<=255 to 0<=sensor_value<=1023
14     print("original sensor value: ", sensor_value)
15     mapped_value = simpleio.map_range(sensor_value, 0, 255, 0, 1023)
16     print("mapped sensor value: ", mapped_value)
17     time.sleep(2)
18
19     # Map the new sensor value back to the old range
20     sensor_value = simpleio.map_range(mapped_value, 0, 1023, 0, 255)
21     print("original value returned: ", sensor_value)
22     time.sleep(2)

```

6.2 simpleio - Simple, beginner friendly IO.

The `simpleio` module contains classes to provide simple access to IO.

- Author(s): Scott Shawcroft

class `simpleio.DigitalIn` (*pin*, ***kwargs*)

Simple digital input that is valid until reload.

param pin `microcontroller.Pin` input pin

param pull `digitalio.Pull` pull configuration for the input

value

The digital logic level of the input pin.

class `simpleio.DigitalOut` (*pin*, ***kwargs*)

Simple digital output that is valid until reload.

param pin `microcontroller.Pin` output pin

param value `bool` default value

param drive_mode `digitalio.DriveMode` drive mode for the output

value

The digital logic level of the output pin.

`simpleio.bitWrite` (*x*, *n*, *b*)

Based on the Arduino `bitWrite` function, changes a specific bit of a value to 0 or 1. The return value is the original value with the changed bit. This function is written for use with 8-bit shift registers

Parameters

- **x** – numeric value
- **n** – position to change starting with least-significant (right-most) bit as 0
- **b** – value to write (0 or 1)

`simpleio.map_range` (*x*, *in_min*, *in_max*, *out_min*, *out_max*)

Maps a number from one range to another. Note: This implementation handles values < *in_min* differently than arduino's `map` function does.

Returns Returns value mapped to new range

Return type `float`

`simpleio.shift_in` (*data_pin*, *clock*, *msb_first=True*)

Shifts in a byte of data one bit at a time. Starts from either the LSB or MSB.

Warning: Data and clock are swapped compared to other CircuitPython libraries in order to match Arduino.

Parameters

- **data_pin** (`DigitalInOut`) – pin on which to input each bit
- **clock** (`DigitalInOut`) – toggles to signal *data_pin* reads
- **msb_first** (`bool`) – True when the first bit is most significant

Returns returns the value read

Return type `int`

`simpleio.shift_out(data_pin, clock, value, msb_first=True, bitcount=8)`

Shifts out a byte of data one bit at a time. Data gets written to a data pin. Then, the clock pulses hi then low

Warning: Data and clock are swapped compared to other CircuitPython libraries in order to match Arduino.

Parameters

- **data_pin** (*DigitalInOut*) – value bits get output on this pin
- **clock** (*DigitalInOut*) – toggled once the data pin is set
- **msb_first** (*bool*) – True when the first bit is most significant
- **value** (*int*) – byte to be shifted
- **bitcount** (*unsigned*) – number of bits to shift

Example for Metro M0 Express:

```
import digitalio
import simpleio
from board import *
clock = digitalio.DigitalInOut(D12)
data_pin = digitalio.DigitalInOut(D11)
latchPin = digitalio.DigitalInOut(D10)
clock.direction = digitalio.Direction.OUTPUT
data_pin.direction = digitalio.Direction.OUTPUT
latchPin.direction = digitalio.Direction.OUTPUT

while True:
    valueSend = 500
    # shifting out least significant bits
    # must toggle latchPin.value before and after shift_out to push to IC chip
    # this sample code was tested using
    latchPin.value = False
    simpleio.shift_out(data_pin, clock, (valueSend>>8), msb_first = False)
    latchPin.value = True
    time.sleep(1.0)
    latchPin.value = False
    simpleio.shift_out(data_pin, clock, valueSend, msb_first = False)
    latchPin.value = True
    time.sleep(1.0)

    # shifting out most significant bits
    latchPin.value = False
    simpleio.shift_out(data_pin, clock, (valueSend>>8))
    latchPin.value = True
    time.sleep(1.0)
    latchPin.value = False
    simpleio.shift_out(data_pin, clock, valueSend)
    latchPin.value = True
    time.sleep(1.0)
```

`simpleio.tone(pin, frequency, duration=1, length=100)`

Generates a square wave of the specified frequency on a pin

Parameters

- **pin** (*Pin*) – Pin on which to output the tone

- **frequency** (*float*) – Frequency of tone in Hz
- **length** (*int*) – Variable size buffer (optional)
- **duration** (*int*) – Duration of tone in seconds (optional)

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`

S

`simpleio`, [14](#)

B

`bitWrite()` (*in module simpleio*), 15

D

`DigitalIn` (*class in simpleio*), 15

`DigitalOut` (*class in simpleio*), 15

M

`map_range()` (*in module simpleio*), 15

S

`shift_in()` (*in module simpleio*), 15

`shift_out()` (*in module simpleio*), 16

`simpleio` (*module*), 14

T

`tone()` (*in module simpleio*), 16

V

`value` (*simpleio.DigitalIn attribute*), 15

`value` (*simpleio.DigitalOut attribute*), 15